

# TRANEMO

ADVANCED WORKWEAR





EN ISO 11612  
A1+A2 B1 C2 F1



EN 61482-2  
APC 2

ELIM: 32,0 cal/cm<sup>2</sup> ATPV: 32,0 cal/cm<sup>2</sup>



EN 1149-5



\*EN ISO 11611  
CL.1 A1+A2



\*EN 13034  
type PB[6]



EN ISO 20471  
CL.3 CL.2\*\*\* (XXS-XS)



EN 343  
4.1



\*\*EN 342  
(5109+5122)

\*Hood must be used or removed during welding or work with chemicals.

\*\*The garment is tested in a 3 layer system together with basic underwear. Tranemo recommends underwear 592092/594092 and 598089.

\*\*\*The garment has a combined certification and is approved for EN ISO 20471 CL.3 when worn together with Tranemo trousers or bib'n'brace certified according to EN ISO 20471 CL.1 or CL.2.

<sup>1</sup>This garment is produced with new PFAS-free fabrics. For a period, we will have a mixed stock and the transition to PFAS-free will be a running replacement.

## 51099394 FLAME RETARDANT WINTER JACKET, HOOD

PFAS-free<sup>1</sup>, non-metal and inherent flame retardant high visibility winter jacket with removable hood, taped seams and quilted lining. Wind and waterproof according to EN 343. Outer fabric with 20% recycled fibres.

Adjustable and removable hood with quilted lining. Hidden zip and stud fastener in front. Two loops for communication equipment. Vertical chest pocket with zip on right chest. D-ring. Side pockets with fleece lining and pocket flaps. Extended back with two side slits for enhanced movement. Adjustable cuffs. Wind stoppers in sleeves. Inside pockets, one for Ipad/documents. Fleece on the inside of the collar. Zip access for back heat seal badges. Special order – please allow an additional 5 days approximately.

**Colour:** 94 yellow/navy

**Size:** XXS-4XL

**Quality:** 932 - Cantex 240IR Recycled - 50% modacrylic / 43% cotton / 6% polyamide / 1% antistatic, PU-laminated, 300 g/m<sup>2</sup>

055 - Lining - Quilt FR, 45% modacrylic / 35% cotton / 18% polyamide / 2% antistatic, 160 g/m<sup>2</sup> with polyester wadding, 110 g/m<sup>2</sup>

054 - Lining - Quilt FR, 45% modacrylic / 35% cotton / 18% polyamide / 2% antistatic, 160 g/m<sup>2</sup> with polyester wadding, 80 g/m<sup>2</sup>

