TRANEMO

ADVANCED WORKWEAR



CE

EN ISO 11612
A1 B1 C1 F1

EN 61482-2
APC 2

ELIM: 20,0 cal/cm² ATPV: 21,0 cal/cm²

EN 1149-5

**EN ISO 11611
CL.1 A1

**EN 13034
type PB[6]

EN ISO 20471
CL.3 CL.2* (XS-S)

EN 343
3.3

*The garment has a combined certification and is approved for EN ISO 20471 CL.3 when worn together with Tranemo trousers or bib´n´brace certified according to EN ISO 20471 CL.1 or CL.2.

**Hood must be used or removed during welding or work with chemicals.

513694 FLAME RETARDANT SHELL JACKET + LINING 9128

Non-metal, inherent flame retardant shell jacket with taped seams and mesh lining. Comes with sleeveless fibrefur lining 9128 06. Wind and waterproof according to EN 343.

The jacket is ergonomically shaped for work with raised arms. Concealed front zip and double storm flap with press studs. Detachable and adjustable hood. Two loops for communication equipment. Chest pockets with zip. D-ring. Two inside pockets with zip, one for documents/Ipad with an integrated mobile phone pocket. Inside headset holder. Side pockets with zip. Adjustable sleeve width and inside knitted cuffs in sleeves. Drawcord at the bottom of the jacket. HTFR Dobby at the bottom of the jacket and on the sleeves. Heat sealed reflective stripes for greater comfort. Fiberfur lining 9128.

Size: XS-4XL

Quality: 943 - Mega TX 230IR - 59% viscose / 40% modacrylic / 1% antistatic, PU-laminated, 230 g/m²
804 - HTFR Dobby - 39% modacrylic / 28% polyamide / 17% cotton / 15% aramid / 1% antistatic, 295 g/m²
805 - FR Mesh - 98% aramid / 2% antistatic, 110 g/m²
911 - Tera TX Light - 45% modacrylic / 35% cotton / 18% polyamide / 2% antistatic, 160 g/m²
0613 - Removable lining - Pile FR, 87% modacrylic / 13% cotton, 360 g/m²



OEKO TEX® STANDARD 100 PPE 2476-423PPE DTI
www.oeko-tex.com